


## ECD® 'Elite Series' Skirting Duct

### AT A GLANCE...

- Size: 150 x 75 mm
- Stock Colours: Grey, Black, White & Natural Anodised
- Suitable for: Category 6A & 7 Cabling
- Cable Capacity: See chart over leaf

- Suitable for categories 6A and 7 data cabling.
- Drop In cover (also available with "Clip In" cover).
- Extruded aluminium body.
- All outlets centrally mounted (suits power packs).
- Die-cast power shroud (easy fitting).
- Spacious data "fit-off" zone.
- Die-cast external/internal bends.
- Conforms to AS 3000 and A.C.M.A. requirements.
- Non standard powdercoat colours available.
- Bend radius available.
- Optional divider (2 or 3 division).
- Fully or semi recessed trims available.



FULL SIZE SECTION

**"Easy as ECD®"**



ESTABLISHED 1979

**Electric Cable Duct Systems P/L**


Phone: 1300 123 ECD (323)

Email: [info@ecd.net.au](mailto:info@ecd.net.au)

Fax: 1300 372 825

website: [www.ecd.net.au](http://www.ecd.net.au)

ABN 80005544105



## SUGGESTED SPECIFICATION

- The contractor shall allow to supply and install Electric Cable Duct Systems P/L ECD® 'ELITE SERIES' Cat No. EL15075D skirting duct and cover (150x75mm) surface mounted or as otherwise nominated.
- The body of the duct shall be extruded aluminium pre-treated and powdercoated to a standard colour (White, APO Grey, Black or Natural Anodised) or as nominated by the architect. The duct cover shall be pre-treated electro-galvanised steel powdercoated to match duct body or natural anodised.
- The system shall be earthed in accordance with AS 3000 wiring rules and conform to A.C.M.A. requirements.
- The internal/external corners shall be fitted with die-cast bends or site mitred.
- Adjacent lengths of duct body shall be splice joined with slide in joiner plates and earth continuity plates.
- Stop ends shall be fitted where necessary.
- GPOs shall be mounted to the duct body using GPO mounting kits including die-cast shroud, earth wire and punched front cover. Power circuits within the duct shall be double insulated cable.
- Data outlets shall be mounted to the duct body using data mounting kits including data bracket and punched front cover.

## PARTS LIST

DESCRIPTION	PART NO.	COLOUR
Duct body and Drop-in cover (3m lengths) incl. joining kit	EL15075DD	Nominate (see below)
Internal/External Bend (Die-cast)	EL15075B	Nominate (see below)
Stop End	EL15075SE	Nominate (see below)
GPO Kit (Drop In) c/w die-cast power shroud	EL150DPK	Nominate (see below)
Data Kit (Drop In) c/w data bracket	EL150DDK	Nominate (see below)
Flat Bend Joiner	ELFBJ	
Cat 6A Angled Data Face Plate	88DP2	Nominate (see below)
Divider (optional) for 3 division	EL75DB	
Bend Radius	EL150BR	

Nominate Colour/Finish: BK=Black, WE=White, GY=Apo Grey, NA=Natural Anodised

## CABLE CAPACITY CHART (ALLOWS FOR 60% AIR SPACE)

POWER CABLES		DATA CABLES		
2.5 mm <sup>2</sup>	4.0 mm <sup>2</sup>	Cat. 5E	Cat. 6	Cat. 6A
25	12	108	64	40