PROTECTOR™ SERIES Flush Floor Box

Flush, Square Edged, Stainless Steel

AT A GLANCE…

- Capacity: 2 standard sized plates
- Box Size: 240 x 150 x 110 mm Deep
- Features: • **Cable Shield**® Frame
  • Soft close lid
- Lid Material: Stainless 304 – No. 4 Linished
- Suitable for: Cat6A & 7A Cabling

"Easy as ECD®"

- Flush Protector™ Series Stainless Steel Lid and Frame with No. 4 Linished finish.

- Frame has square edges (not bevelled) to allow flush fitting to adjacent floor finish (typically timber, tiles or vinyl).

- Protector™ Series features
  - **Cable Shield**® Frame assembly to prevent cables being cut. (Patent Certified 2017100897 & Patent Pending 2015204344)
  - Soft close lid to stop lid from slamming shut
  - Cable retainer for easy cable management.

- Robust and large capacity cable exit flap with retracing lifting handle.

- Capacity for 2 standard outlet plates. (1 x double power & 1 x Data and/or A.V.)

- Suitable for category 6A and 7A data cabling with generous bend radius capacity.

- Suitable for Audio / Video outlets including VGA, HDMI, USB, etc.

  - 304 Grade Solid Stainless Steel.

  - Modular box body and lid design, interchangeable with plastic and other lids in the ECD® floor box range.

  - Supplied with temporary construction lid.

  - Option to fit cam lock if required.

ECD®

ESTABLISHED 1979

Electric Cable Duct Systems P/L

Phone: 1300 123 ECD (323)   Fax: 1300 372 825
Email: info@ecd.net.au   website: www.ecd.net.au

ASSEMBLY DIAGRAM

PROTECTOR™ SERIES FLUSH FLOOR BOX – FLUSH, SQUARE EDGE, STAINLESS STEEL – FB2SQF

CABLE SHIELD®
FRAME ASSEMBLY

FB2SQF SQUARE EDGE STAINLESS STEEL
FLUSH LID AND FRAME ASSEMBLY WITH
CABLE SHIELD® FRAME, SOFT CLOSER, CABLE
EXIT, RUBBER DUST SEAL AND RECESSED
LIFTING HANDLE
(OVERALL LID SIZE 266 x 176)

OUTLET MOUNTING
BRACKET TO SUIT 1 No.
DOUBLE GPOs

OUTLET MOUNTING BRACKET
TO SUIT 1 No. STANDARD
DATA GRID PLATE

DATA PLATE VIEW

110
(INCL. LID)
95
15

STEEL BOX BODY
(240 x 150 x 110mm DEEP)
12 No. 25ø/32ø COMBINATION
CONDUIT KNOCKOUTS

OPTIONAL TIMBER FLOOR
FIXING BRACKETS
PART No. FBTFB

240

150

NOMINAL RECESS SIZE
250 x 160 x 120 DEEP FOR TIMBER FLOOR OR
300 x 200 x 120 FOAM BLOCKOUT FOR
CONCRETE

SECTION THRU' BOX

110

POWER | DATA

240

60

CONDUIT LOCATION BOX BASE

240
25 | 190 | 25
150
40
70
40

CONDUIT LOCATION HINGE & EXIT SIDES

240
25 | 190 | 25
15
95
70
25
TEMPORARY LID

CONDUIT LOCATION OUTLET SIDES

150
40 | 70 | 40
15
95
52
43