PROTECTOR™ SERIES Flush Floor Box Flush, Stainless Steel

AT A GLANCE…

- **Capacity:** 2 standard sized plates
- **Box Size:** 240 x 150 x 110mm deep
- **Features:** Rubber exit flap to all 3 sides
- **Lid Material:** Stainless 304 – No. 4 Linished
- **Suitable for:** Cat6A & 7A Cabling
- **Load Rating:** 120kg (per foot = foot traffic)

"Easy as ECD®"

- Flush Protector™ Series stainless steel lid and frame with No. 4 Linished finish.
- Protector™ Series features
  - **Cable Shield®** Frame assembly to prevent cables being cut – lid frame only.
    (Patent Certified 2019268210 & 2015204344)
  - Soft close lid to stop lid from slamming shut.
- Rubber cable exit flaps to all three sides enables cables to safely exit the lid at any point.
- Capacity for 2 standard outlet plates (1 x double power and 1 x data and/or A.V.).
- Suitable for category 6A and 7A data cabling with generous bend radius capacity.
- Suitable for Audio / Video outlets including VGA, HDMI, USB, etc.
- 304 Grade solid stainless steel with No. 4 Linished finish to meet P1 requirements for slip resistance in public spaces (dry areas).
- Modular box body and lid design, interchangeable with plastic and other lids in the ECD® floor box range.
- Supplied with temporary construction lid.
- Option to fit cam lock if required (Ref. FB2MUCL).

ECD®
ESTABLISHED 1979

Electric Cable Duct Systems P/L
Phone: 1300 123 ECD (323)   Fax: 1300 372 825
Email: info@ecd.net.au   website: www.ecd.net.au

ABN 80005544105

2024

ASSEMBLY DIAGRAM

PROTECTOR™ SERIES FLUSH FLOOR BOX – FLUSH, STAINLESS STEEL – FB2MU

RUBBER CABLE EXIT FLAPS
TO 3 SIDES

FB2MU 'PROTECTOR' STAINLESS STEEL
FLUSH LID AND FRAME ASSEMBLY WITH
SOFT CLOSER, RUBBER CABLE EXITS TO
3 SIDES AND RECESSED LIFTING HANDLE
(OVERALL LID SIZE 266 x 176)

CABLE SHIELD® FRAME ASSEMBLY

176

266

OUTLET MOUNTING
BRACKET TO SUIT 1 No.
DOUBLE GPO

OUTLET MOUNTING BRACKET
TO SUIT 1 No. STANDARD DATA
GRID PLATE

DATA PLATE

110 INC. LID
15
95

OPTIONAL TIMBER FLOOR
FIXING BRACKETS
(PART No. FBTFB)

STEEL BOX BODY
(240 x 150 x 110mm DEEP)
12 No. 25ø/32ø COMBINATION
CONDUIT KNOCKOUTS

240

150

NOMINAL RECESS SIZE
250 x 160 x 120 DEEP FOR TIMBER
FLOOR OR 300 x 200 x 120 FOAM
BLOCKOUT FOR CONCRETE
(PART No. FB2F)

110 | POWER | DATA
240 | 60

SECTION THRU' BOX

CONDUIT LOCATION BOX BASE

240
25 190 25
150
40 70 40
15

CONDUIT LOCATION HINGE & EXIT SIDES

240
25 190 25
TEMPORARY LID
95 70
25
15

CONDUIT LOCATION OUTLET SIDES

150
40 70 40
95 52
43