Flush Floor Box Deep Recessed, Brass, Soft Close

AT A GLANCE...

Capacity: 4 x single auto switch power

outlets and 6 x data

■ Box Size: 250 x 250 x 93mm deep

(c/w-Lid)

■ Lid Material: Brass – No. 4 Linished

Lid Recess: 20mm deepSuitable for: Cat6A & 7A Cabling

OMPA

■ Load Rating: 120kg (per foot = foot traffic)

- Recessed brass lid and frame with 20mm rebate for floor finish (typically polished timber boards or ceramic tiles).
- Solid brass lid construction with No. 4 Linished finish.
- Adjustable Soft Closer to control lid closure suits floor finish infills up to 1kg (eg. timber packer & carpet or full timber).
- Optional Gas Strut kit available to suit heavier floor finish infills from 2kg (eg. ceramic tile) to 4kg (eg. stone). Custom heavier Gas Strut kits available to order.
- Frame has square edges (not beveled) to allow flush fitting to adjacent floor finish.
- Height adjustable lid and frame.
- Robust, large capacity cable exit flap with CableShield and brass lifting handle.
- Capacity for 4 x single auto switch power outlets (supplied pre-wired) and 6 x data (bezels supplied).
- Suitable for category 6A and 7A data cabling with generous bend radius capacity.
- Suitable for Audio / Video outlets including VGA, HDMI, USB, etc.
 - Modular box body and lid design, interchangeable with plastic and other lids in the ECD® floor box range.
 - Supplied with temporary construction lid.





"Easy as ECD""



Electric Cable Duct Systems P/L

Phone: 1300 123 ECD (323) Fax: 1300 372 825

Email: info@ecd.net.au website: www.ecd.net.au

ABN 80005544105



ASSEMBLY DIAGRAM

FLUSH FLOOR BOX - DEEP RECESSED, BRASS, SOFT CLOSE - FB4BDR70

