PROTECTOR™ SERIES Flush Floor Box Flush, Stainless Steel

AT A GLANCE…

- **Capacity:** 8 x auto switch GPOs and 2 x standard sized plates
- **Box Size:** 240 x 240 x 110 mm deep
- **Features:** Rubber exit flap to all 3 sides
- **Lid Material:** Stainless 304 – No. 4 Linished
- **Suitable for:** Cat6A & 7A Cabling

"Easy as ECD®"

- Flush Protector™ Series 304 grade Stainless Steel lid and frame with No. 4 Linished finish.

- Protector™ Series features
  - **Cable Shield**® Frame assembly to prevent cables being cut – lid frame only.
    (Patent Certified 2017100897 & Patent Pending 2015204344)
  - Soft close lid to stop lid from slamming shut.

- Rubber cable exit flaps to all three sides enables cables to safely exit the lid at any point.

- Capacity for 8 x auto switch GPOs (supplied) and 2 x standard sized data plates.

- Suitable for category 6A and 7A data cabling with generous bend radius capacity.

- Suitable for Audio / Video outlets including VGA, HDMI, USB, etc.

- Modular box body and lid design, interchangeable with plastic and other lids in the ECD® floor box range.

  - Supplied with temporary construction lid.
  - Option to fit cam lock if required (Ref. FB4MUCL8P).

ECD®

ESTABLISHED 1979

Electric Cable Duct Systems P/L
Phone: 1300 123 ECD (323)   Fax: 1300 372 825
Email: info@ecd.net.au   website: www.ecd.net.au

ABN 80005544105

2022

ASSEMBLY DIAGRAM

PROTECTOR™ SERIES FLUSH FLOOR BOX – FLUSH STAINLESS STEEL – FB4MU8P

RUBBER CABLE EXIT FLAPS TO 3 SIDES

CABLE SHIELD® FRAME ASSEMBLY

FB4MU 'PROTECTOR' STAINLESS STEEL FLUSH LID AND FRAME ASSEMBLY WITH SOFT CLOSER, RUBBER CABLE EXITS TO 3 SIDES AND RECESSED LIFTING HANDLE (OVERALL LID SIZE 266 x 266)

OUTLET MOUNTING BRACKET TO SUIT 8 No. AUTO SWITCH GPOs

LID SUPPORT POST

OUTLET MOUNTING BRACKET TO SUIT 2 No. STANDARD DATA GRID PLATES

DATA PLATE VIEW

OPTIONAL TIMBER FLOOR FIXING BRACKETS

STEEL BOX BODY (240 x 240 x 110mm DEEP) 12 No. 25ø/32ø COMBINATION CONDUIT KNOCKOUTS

NOMINAL RECESS SIZE 250 x 250 x 120 DEEP FOR TIMBER FLOOR OR 300 x 300 x 120 FOAM BLOCKOUT FOR CONCRETE

CONDUIT LOCATION BOX BASE

CONDUIT LOCATION HINGE & EXIT SIDES

CONDUIT LOCATION OUTLET SIDES

TEMPORARY LID

POWER   DATA

SECTION THRU' BOX