# PROTECTOR™ SERIES Flush Floor Box Recessed, Stainless Steel

AT A GLANCE…

- **Capacity:** 8 x auto switch GPOs and 2 standard sized plates
- **Box Size:** 240 x 240 x 110 mm Deep
- **Features:**
  - Cable Shield® Frame
  - Soft close lid
- **Lid Material:** Stainless 304 – No. 4 Linished
- **Recess:** 6 mm Deep
- **Suitable for:** Cat6A & 7A Cabling

"Easy as ECD®"

- Recessed Protector™ Series Stainless Steel Lid and Frame with 6 mm rebate for floor finish (typically carpet or vinyl).
- Protector™ Series features
  - **Cable Shield®** Frame assembly to prevent cables being cut. (Patent Certified 2017100897 & Patent Pending 2015204344)
  - Soft close lid to stop lid from slamming shut
  - Cable retainer for easy cable management.
- Robust and large capacity cable exit flap with retracing lifting handle.
- Capacity for 8 Auto Switch GPOs & 2 standard Data plates (8 x power & 2 x Data and/or A.V.).
- Suitable for category 6A and 7A data cabling with generous bend radius capacity.
- Suitable for Audio / Video outlets including VGA, HDMI, USB, etc.
- 304 Grade Solid Stainless Steel with No. 4 Linished finish.
- Modular box body and lid design, interchangeable with plastic and other lids in the ECD® floor box range.
- Supplied with temporary construction lid.
- Option to fit cam lock if required.

Electric Cable Duct Systems P/L

Phone: 1300 123 ECD (323)   Fax: 1300 372 825
Email: info@ecd.net.au   website: www.ecd.net.au

ESTABLISHED 1979

ABN 80005544105

ASSEMBLY DIAGRAM

PROTECTOR™ SERIES FLUSH FLOOR BOX – RECESSED STAINLESS STEEL – FB4SR8P

FB4SR STAINLESS STEEL RECESSED LID AND FRAME ASSEMBLY WITH *CABLE SHIELD*® FRAME, SOFT CLOSER, CABLE EXIT, RUBBER DUST SEAL AND RECESSED LIFTING HANDLE (OVERALL LID SIZE 266 x 266)

CABLE SHIELD® FRAME ASSEMBLY

266

266

266

OUTLET MOUNTING BRACKET TO SUIT 8 No. AUTO SWITCH GPOs

OUTLET MOUNTING BRACKET TO SUIT 2 No. STANDARD DATA GRID PLATES

DATA PLATE VIEW

110 (INC. LID)

95

15

STEEL BOX BODY
(240 x 240 x 110mm DEEP)
12 No. 25ø/32ø COMBINATION CONDUIT KNOCKOUTS

OPTIONAL TIMBER FLOOR FIXING BRACKETS
PART No. FBTFB

240

240

NOMINAL RECESS SIZE
250 x 250 x 120 DEEP FOR TIMBER FLOOR OR
300 x 300 x 120 FOAM BLOCKOUT FOR CONCRETE

110

POWER | DATA

240

60

SECTION THRU' BOX

CONDUIT LOCATION BOX BASE

240
25 | 190 | 25
240
60
120
60

CONDUIT LOCATION HINGE & EXIT SIDES

15
240
25 | 190 | 25
TEMPORARY LID
95
70
25

CONDUIT LOCATION OUTLET SIDES

15
240
60 | 120 | 60
95
52
43